

Solution / marking scheme – Water and Objects (10 pt)

General rules

- In the following, “coefficients” refer to the numerical factors and do not include parameters.

Part A. Merger of water drops (2.0 pt)

A.1 (total 2.0 pt)

(2.0 pt)

$$v = 0.23 \text{ m/s}$$

- No deduction if the answer falls within the range $0.22 \text{ m/s} \leq v \leq 0.24 \text{ m/s}$

————— partial points —————

The surface energy per drop before the merger:

$$(0.4 \text{ pt}) \quad E = 4\pi a^2 \gamma \quad (\text{A.1.1})$$

The surface energy difference:

$$(0.6 \text{ pt}) \quad \Delta E = 4\pi (2 - 2^{2/3}) a^2 \gamma \quad (\text{A.1.2})$$

The transfer of surface energy to kinetic energy :

$$(0.4 \text{ pt}) \quad Mv^2/2 = k\Delta E \quad (\text{A.1.3})$$

where $M = 4\pi a^3 \rho/3 \times 2 = 8\pi a^3 \rho/3$ is the mass of the drop after the merger.

- No partial point will be given if the factor k is missing.

Numerical evaluation:

$$v = \sqrt{\frac{2k\Delta E}{M}} = \sqrt{3(2 - 2^{2/3}) \frac{k\gamma}{\rho a}} = \sqrt{3(2 - 2^{2/3}) \times \frac{0.06 \times (7.27 \times 10^{-2})}{(1.0 \times 10^3) \times (100 \times 10^{-6})}} = 0.23 \text{ m/s}$$

Part B. A vertically placed board (4.5 pt)

B.1 (total 0.6 pt)Usable letters: ρ, g, z, P_0

(0.6 pt)

$$P = P_0 - \rho g z$$

- No point will be given for $P = P_0 + \rho g z$

— Commentary —

The expression, $P = P_0 - \rho g z$, holds for both $z < 0$ and $z > 0$, as long as z is inside the water.

B.2 (total 0.8 pt)Usable letters: ρ, g, z_1, z_2

(0.8 pt)

$$f_x = \frac{1}{2} \rho g (z_2^2 - z_1^2)$$

- Give 0.6 pt for $f_x = \rho g (z_2^2 - z_1^2)$
- Give 0.4 pt for $f_x = \frac{1}{2} \rho g (z_1^2 - z_2^2)$

— Commentary —

Because the atmospheric pressure P_0 exerts no net horizontal force on the water block, we have

$$f_x = \int_{z_2}^{z_1} (-\rho g z) dz = \frac{1}{2} \rho g (z_2^2 - z_1^2)$$

B.3 (total 0.8 pt)Usable letters: $\gamma, \theta_1, \theta_2$

(0.8 pt)

$$f_x = \gamma \cos \theta_1 - \gamma \cos \theta_2$$

- Give 0.6 pt for $f_x = \gamma \cos \theta_2 - \gamma \cos \theta_1$
- Give 0.4 pt for $f_x = \gamma \cos \theta_2 + \gamma \cos \theta_1$ or $f_x = -\gamma \cos \theta_2 - \gamma \cos \theta_1$.

B.4 (total 0.8 pt)

(0.4 pt)

$$a = 2$$

- No point will be given for $a \neq 2$.

Usable letters: γ, ρ

(0.4 pt)

$$\ell = \sqrt{\frac{\gamma}{\rho g}}$$

- If an unnecessary coefficient is included as a factor, 0.2 pt will be deducted.

B.5 (total 1.5 pt)Usable letters: $\tan \theta_0, \ell$

(1.5 pt)

$$z(x) = -\ell \tan \theta_0 e^{-x/\ell}$$

- Deduct 0.2 pt for $z(x) = -\ell \sin \theta_0 e^{-x/\ell}$ or $z(x) = -\ell \theta_0 e^{-x/\ell}$.

————— partial points —————

 $z' = \tan \theta$ leads to

$$(0.2 \text{ pt}) \quad \cos \theta = \frac{1}{\sqrt{1 + (z')^2}} \quad (\text{B.5.1})$$

$$(0.1 \text{ pt}) \quad \cos \theta \simeq 1 - \frac{1}{2}(z')^2 \quad (\text{B.5.2})$$

Plug this into Eq.(1) to obtain,

$$(0.2 \text{ pt}) \quad \frac{z^2}{\ell^2} - z'^2 = \text{const.} \quad (\text{B.5.3})$$

Take the derivative of both sides with respect to x :

$$(0.5 \text{ pt}) \quad z'' = \frac{z}{\ell^2} \quad (\text{B.5.4})$$

which is the differential equation which determines the water surface form.

General solution:

$$(0.2 \text{ pt}) \quad z = Ae^{x/\ell} + Be^{-x/\ell} \quad (\text{B.5.5})$$

The boundary condition, $z(\infty) = 0$, leads to

$$(0.1 \text{ pt}) \quad A = 0 \quad (\text{B.5.6})$$

The boundary condition, $z'(0) = \tan \theta_0$, leads to

$$(0.2 \text{ pt}) \quad B = -\ell \tan \theta_0 \quad (\text{B.5.7})$$

Part C. Interaction between two rods (3.5 pt)

C.1 (total 1.0 pt)

Usable letters: $\theta_a, \theta_b, z_a, z_b, \rho, g, \gamma$

(1.0 pt)

$$F_x = \frac{1}{2} \rho g (z_b^2 - z_a^2) + \gamma (\cos \theta_b - \cos \theta_a)$$

- Give 0.8 pt for $F_x = \frac{1}{2} \rho g (z_b^2 - z_a^2) + \gamma (\cos \theta_a - \cos \theta_b)$
- Give 0.6 pt for $F_x = \frac{1}{2} \rho g (z_b^2 - z_a^2) + \gamma \cos \theta_2 + \gamma \cos \theta_1$ or $F_x = \frac{1}{2} \rho g (z_b^2 - z_a^2) - \gamma \cos \theta_2 - \gamma \cos \theta_1$.

————— partial points —————

The horizontal component of the force due to the pressure is

$$(0.6 \text{ pt}) \quad \int_{z_a}^{z_b} (\rho g z) dz = \frac{1}{2} \rho g (z_b^2 - z_a^2) \quad (\text{C.1.1})$$

————— Commentary —————

Comment 1: How to apply the experience in B.1 is as follows. Let z_{bottom} the z -coordinate at the bottom of the rod, then from the discussion in B1, we see

$$F_x = \int_{z_{\text{bottom}}}^{z_a} (-\rho g z) dz + \left(- \int_{z_{\text{bottom}}}^{z_b} (-\rho g z) dz \right) = \int_{z_a}^{z_b} (\rho g z) dz$$

Comment 2: The fact that the contribution due to the pressure does not depend on the shape of the cross-section can be demonstrated as follows. The pressure at the point s on the contour C along the cross-sectional boundary is


$$-P \hat{n} ds = (-P_0 + \rho g) \hat{n} ds.$$

Let \hat{x} the unit vector pointing the positive x -direction and noting $\hat{x} \cdot \hat{n} ds = dz$ (see the figure shown below), the horizontal component becomes and its horizontal component becomes

$$-P \hat{n} \cdot \hat{x} ds = -P_0 dz + \rho g dz.$$

Integrating along the contour C , we obtain

$$\oint_C (-P \hat{n} \cdot \hat{x} ds) = \int_{z_a}^{z_b} (\rho g z) dz = \frac{1}{2} \rho g (z_b^2 - z_a^2)$$



C.2 (total 1.5 pt)Unusable letters: $\theta_a, \theta_b, z_a, z_b$

(1.5 pt)

$$F_x = -\frac{1}{2}\rho g z_0^2$$

- Give 1.3 pt for $F_x = -\rho g z_0^2$.
- Give 0.8 pt for $F_x = \frac{1}{2}\rho g z_0^2$.

———— partial points ————

Apply the boundary conditions to Eq. (1) to obtain

$$(0.6 \text{ pt}) \quad \underbrace{\frac{1}{2}\rho g z_a^2 + \gamma \cos \theta_a}_{x=x_a} = \underbrace{\frac{1}{2}\rho g z_0^2 + \gamma}_{x=0} \quad (\text{C.2.1})$$

- Give 0.4 pt for $\rho g z_a^2 + \gamma \cos \theta_a = \rho g z_0^2 + \gamma$

$$(0.6 \text{ pt}) \quad \underbrace{\frac{1}{2}\rho g z_b^2 + \gamma \cos \theta_b}_{x=x_b} = \underbrace{\gamma}_{x \rightarrow \infty} \quad (\text{C.2.2})$$

- Give 0.4 pt for $\rho g z_b^2 + \gamma \cos \theta_b = \rho g z_0^2$

 F_x is obtained by subtracting (C2.1) from (C2.2).

C.3 (total 1.0 pt)

Usable letters: x_a, z_a

(1.0 pt)

$$z_0 = \frac{2z_a}{e^{x_a/\ell} + e^{-x_a/\ell}}$$

- Correct alternative answer: $z_0 = \frac{z_a}{\cosh(x_a/\ell)} = z_a \operatorname{sech}(x_a/\ell)$

————— partial points —————

General solution: $z(x) = Ae^{x/\ell} + Be^{-x/\ell}$

Taking into account the left-right symmetry, we obtain,

$$(0.3 \text{ pt}) \quad A = B \tag{C.3.1}$$

Boundary condition, $z(0) = z_0$ leads to

$$(0.3 \text{ pt}) \quad A + B = z_0 \tag{C.3.2}$$

Find the coefficients:

$$(0.2 \text{ pt}) \quad A = z_0/2 \tag{C.3.3}$$

$$(0.2 \text{ pt}) \quad B = z_0/2 \tag{C.3.4}$$